


LUMINAIRE PHOTOMETRIC TEST REPORT

Test:U:230.71V I:0.0512A P:6.0445W PF:0.5115 Freq:50.00Hz Lamp Flux:748.8x1 lm		
NAME: NEBULA MINI - BRACKET	TYPE:LANDSCAPE LUMINAIRES	WEIGHT:
SPEC.:WW, LUMILED, BA-25°	DIM.: 101 x 64 x 93	SERIAL No.:4785
MFR.: K-LITE	SUR.:	Shielding Angle:

DATA OF LAMP		PHOTOMETRIC DATA			
MODEL	KL-4266	Imax (cd)	2240	S/MH (C0/180)	0.42
NOMINAL POWER (W)	6	LOR (%)	61.1	S/MH (C90/270)	0.41
RATED VOLTAGE (V)	230	TOTAL FLUX (lm)	457.83	η UP, DN (C0-180)	0.0, 29.5
NOMINAL FLUX (lm)	748.8	CIE CLASS	DIRECT	η UP, DN (C180-360)	0.0, 31.6
LAMPS INSIDE	1	η up (%)	0.0	CIBSE SHR NOM	0.00
TEST VOLTAGE (V)	230	η down (%)	61.1	CIBSE SHR MAX	1.00



C Range: 0 - 360DEG
C Interval: 10.0DEG
Test Speed: HIGH
Temperature: 25.3DEG
Operators: K-LITE
Test Date: 16 August 2022

γ Range: 0 - 90DEG
γ Interval: 1.0DEG
Test System: EVERFINE GO-R5000_V2 SYSTEM V2.00.417
Humidity: 65.0%
Test Distance: 1.852m [K=1.0000]
Remarks: