


LUMINAIRE PHOTOMETRIC TEST REPORT

Test:U:230.62V I:0.1581A P:36.273W PF:0.9947 Freq:49.99Hz Lamp Flux:5527.13x1 lm		
NAME: WALL CYLIN	TYPE:WALL LUMINAIRES	WEIGHT:
SPEC.:WW, CITIZEN, BA-40°	DIM.: 216 x 166 x 200	SERIAL No.:5141
MFR.: K-LITE	SUR.:	Shielding Angle:

DATA OF LAMP		PHOTOMETRIC DATA			
MODEL	KL-3652	Imax (cd)	6157	S/MH (C0/180)	0.58
NOMINAL POWER (W)	40	LOR (%)	55.0	S/MH (C90/270)	0.63
RATED VOLTAGE (V)	230	TOTAL FLUX (lm)	3042.1	η UP, DN (C0-180)	0.0, 25.5
NOMINAL FLUX (lm)	5527.13	CIE CLASS	DIRECT	η UP, DN (C180-360)	0.0, 29.5
LAMPS INSIDE	1	η up (%)	0.0	CIBSE SHR NOM	0.50
TEST VOLTAGE (V)	230	η down (%)	55.0	CIBSE SHR MAX	0.60



C Range: 0 - 360DEG
C Interval: 10.0DEG
Test Speed: HIGH
Temperature: 25.3DEG
Operators: K-LITE
Test Date: 21 November 2022

γ Range: 0 - 90DEG
γ Interval: 1.0DEG
Test System: EVERFINE GO-R5000_V2 SYSTEM V2.00.417
Humidity: 65.0%
Test Distance: 1.852m [K=1.0000]
Remarks: