


LUMINAIRE PHOTOMETRIC TEST REPORT

Test:U:230.51V I:0.2852A P:60.238W PF:0.9162 Freq:49.99Hz Lamp Flux:8539.2x1 lm		
NAME: JUNO	TYPE:POLE MOUNTED SYSTEMS	WEIGHT:
SPEC.:WW, NICHIA	DIM.: Ø600 x 422	SERIAL No.:3819
MFR.: K-LITE	SUR.:	Shielding Angle:

DATA OF LAMP		PHOTOMETRIC DATA			
MODEL	KL-5040	I _{max} (cd)	1846	S/MH (C0/180)	1.13
NOMINAL POWER (W)	60	LOR (%)	56.7	S/MH (C90/270)	1.15
RATED VOLTAGE (V)	230	TOTAL FLUX (lm)	4845.2	η UP, DN (C0-180)	0.3, 27.4
NOMINAL FLUX (lm)	8539.2	CIE CLASS	DIRECT	η UP, DN (C180-360)	0.4, 28.7
LAMPS INSIDE	1	η up (%)	0.7	CIBSE SHR NOM	1.25
TEST VOLTAGE (V)	230	η down (%)	56.0	CIBSE SHR MAX	1.35



C Range: 0 - 360DEG
C Interval: 10.0DEG
Test Speed: HIGH
Temperature: 25.3DEG
Operators: K-LITE
Test Date: 23 November 2021

γ Range: 0 - 180DEG
γ Interval: 1.0DEG
Test System: EVERFINE GO-R5000_V2 SYSTEM V2.00.417
Humidity: 65.0%
Test Distance: 1.825m [K=1.0000]
Remarks: