


LUMINAIRE PHOTOMETRIC TEST REPORT

Test:U:230.01V I:0.0741A P:17.021W PF:0.9725 Freq:50.00Hz Lamp Flux:2131.5x1 lm		
NAME: MUSHROOM	TYPE: BOLLARDS	WEIGHT:
SPEC.: NW, NICHIA	DIM.: Ø168 x 503	SERIAL No.: 2185
MFR.: K-LITE	SUR.:	Shielding Angle:

DATA OF LAMP		PHOTOMETRIC DATA			
MODEL	KL-5583	Imax (cd)	627.5	S/MH (C0/180)	1.21
NOMINAL POWER (W)	16	LOR (%)	68.0	S/MH (C90/270)	1.15
RATED VOLTAGE (V)	230	TOTAL FLUX (lm)	1448.5	η UP, DN (C0-180)	0.0, 34.7
NOMINAL FLUX (lm)	2131.5	CIE CLASS	DIRECT	η UP, DN (C180-360)	0.0, 33.2
LAMPS INSIDE	1	η up (%)	0.0	CIBSE SHR NOM	1.25
TEST VOLTAGE (V)	230	η down (%)	68.0	CIBSE SHR MAX	1.25



C Range: 0 - 360DEG
C Interval: 10.0DEG
Test Speed: HIGH
Temperature: 25.3DEG
Operators: K-LITE
Test Date: 28 October 2020

γ Range: 0 - 90DEG
γ Interval: 1.0DEG
Test System: EVERFINE GO-R5000_V2 SYSTEM V2.00.417
Humidity: 65.0%
Test Distance: 1.825m [K=1.0000]
Remarks: