


LUMINAIRE PHOTOMETRIC TEST REPORT

Test:U:230.66V I:0.0540A P:12.216W PF:0.9810 Freq:49.98Hz Lamp Flux:2073.6x1 lm		
NAME: ZEDO ROUND - SURFACE MOUNTING	TYPE:PATH FINDERS	WEIGHT:
SPEC.:NW, NICHIA	DIM.: Ø180 x 38	SERIAL No.:4932
MFR.: K-LITE	SUR.:	Shielding Angle:

DATA OF LAMP		PHOTOMETRIC DATA			
MODEL	KL-2766	Imax (cd)	591.1	S/MH (C0/180)	1.33
NOMINAL POWER (W)	12	LOR (%)	43.5	S/MH (C90/270)	0.90
RATED VOLTAGE (V)	230	TOTAL FLUX (lm)	902.90	η UP, DN (C0-180)	0.0, 36.4
NOMINAL FLUX (lm)	2073.6	CIE CLASS	DIRECT	η UP, DN (C180-360)	0.0, 7.1
LAMPS INSIDE	1	η up (%)	0.0	CIBSE SHR NOM	0.00
TEST VOLTAGE (V)	230	η down (%)	43.5	CIBSE SHR MAX	1.00



C Range: 0 - 360DEG
C Interval: 10.0DEG
Test Speed: HIGH
Temperature: 25.3DEG
Operators: K-LITE
Test Date: 12 September 2022

γ Range: 0 - 90DEG
γ Interval: 1.0DEG
Test System: EVERFINE GO-R5000_V2 SYSTEM V2.00.417
Humidity: 65.0%
Test Distance: 1.852m [K=1.0000]
Remarks: