


LUMINAIRE PHOTOMETRIC TEST REPORT

| | | |
|---|-------------------------|------------------|
| Test:U:230.64V I:0.1110A P:25.416W PF:0.9931 Freq:49.98Hz Lamp Flux:3977x1 lm | | |
| NAME: CYLIN MIDI | TYPE:CELLING LUMINAIRES | WEIGHT: |
| SPEC.:NW, CITIZEN, BA-15° | DIM.: Ø166 x 200 | SERIAL No.:4917 |
| MFR.: K-LITE | SUR.: | Shielding Angle: |

| DATA OF LAMP | | PHOTOMETRIC DATA | | | |
|-------------------|---------|------------------|--------|---------------------|-----------|
| MODEL | KL-3649 | Imax (cd) | 20898 | S/MH (C0/180) | 0.22 |
| NOMINAL POWER (W) | 25 | LOR (%) | 58.3 | S/MH (C90/270) | 0.23 |
| RATED VOLTAGE (V) | 230 | TOTAL FLUX (lm) | 2317.5 | η UP, DN (C0-180) | 0.0, 29.7 |
| NOMINAL FLUX (lm) | 3977 | CIE CLASS | DIRECT | η UP, DN (C180-360) | 0.0, 28.6 |
| LAMPS INSIDE | 1 | η up (%) | 0.0 | CIBSE SHR NOM | 0.00 |
| TEST VOLTAGE (V) | 230 | η down (%) | 58.3 | CIBSE SHR MAX | 1.00 |



C Range: 0 - 360DEG
C Interval: 10.0DEG
Test Speed: HIGH
Temperature: 25.3DEG
Operators: K-LITE
Test Date: 10 September 2022

γ Range: 0 - 90DEG
γ Interval: 1.0DEG
Test System: EVERFINE GO-R5000_V2 SYSTEM V2.00.417
Humidity: 65.0%
Test Distance: 1.852m [K=1.0000]
Remarks: