



LUMINAIRE PHOTOMETRIC TEST REPORT

Test:U:230.38V I:0.0290A P:6.4316W PF:0.9624 Freq:49.99Hz Lamp Flux:1036.8x1 lm		
NAME: SUDO - OPEN FRAME	TYPE:PATH FINDERS	WEIGHT:
SPEC.:NW, NICHIA	DIM.: 255 x 87 x 76	SERIAL No.:1618
MFR.: K-LITE	SUR.:	Shielding Angle:

DATA OF LAMP		PHOTOMETRIC DATA			Eff: 44.47 lm/W
MODEL	KL-2753	I _{max} (cd)	105.4	S/MH (C0/180)	1.24
NOMINAL POWER (W)	6	LOR (%)	27.6	S/MH (C90/270)	1.23
RATED VOLTAGE (V)	230	TOTAL FLUX (lm)	286.05	η UP, DN (C0-180)	0.0, 13.8
NOMINAL FLUX (lm)	1036.8	CIE CLASS	DIRECT	η UP, DN (C180-360)	0.0, 13.8
LAMPS INSIDE	1	η up (%)	0.0	CIBSE SHR NOM	1.25
TEST VOLTAGE (V)	230	η down (%)	27.6	CIBSE SHR MAX	1.35



C Range: 0 - 360DEG
C Interval: 10.0DEG
Test Speed: HIGH
Temperature: 25.3DEG
Operators: K-LITE
Test Date: 03 August 2020

γ Range: 0 - 90DEG
γ Interval: 1.0DEG
Test System: EVERFINE GO-R5000_V2 SYSTEM V2.00.417
Humidity: 65.0%
Test Distance: 1.944m [K=1.0000]
Remarks: