


LUMINAIRE PHOTOMETRIC TEST REPORT

Test:U:230.20V I:0.0930A P:8.0518W PF:0.3762 Freq:49.99Hz Lamp Flux:600x1 lm		
NAME: ZOOM MICRO	TYPE:FLOOD LIGHTS	WEIGHT:0.570Kg
SPEC.:3000K, MEDIUM BEAM	DIM.: 115 x Ø60 x 160	SERIAL No.:INT/2024/03/31
MFR.: K-LITE	SUR.:	Shielding Angle:

DATA OF LAMP		PHOTOMETRIC DATA			
MODEL	KL-2587	Imax (cd)	1664	S/MH (C0/180)	0.51
NOMINAL POWER (W)	6	LOR (%)	68.5	S/MH (C90/270)	0.48
RATED VOLTAGE (V)	230	TOTAL FLUX (lm)	410.83	η UP, DN (C0-180)	0.0, 34.0
NOMINAL FLUX (lm)	600	CIE CLASS	DIRECT	η UP, DN (C180-360)	0.0, 34.4
LAMPS INSIDE	1	η up (%)	0.0	CIBSE SHR NOM	0.50
TEST VOLTAGE (V)	230	η down (%)	68.5	CIBSE SHR MAX	0.50



C Range: 0 - 360DEG
C Interval: 10.0DEG
Test Speed: HIGH
Temperature: 25.3DEG
Operators: K-LITE
Test Date: 27 March 2024

γ Range: 0 - 90DEG
γ Interval: 1.0DEG
Test System: EVERFINE GO-R5000_V2 SYSTEM V2.00.417
Humidity: 43.1%
Test Distance: 1.997m [K=1.0000]
Remarks: