

Architectural Lighting Pole is design to create a distinctive atmosphere in town & cities by using the most advanced technology to develop innovative lighting solutions. Poles can stylishly convey the identity of any landscape. Our poles can be designed to suit single or multi arms brackets in order to install one or more light sources.

Product Description

- Pole made of continuously tapered circular hot rolled steel grade E250.
- Pole design parameters vary depending on the type of bracket and loading factor.
- Conical pole are welded using saw welding technique by certified welders by using automatic machine with precision welding.
- Other Welding using special v groove technique by certified welders using high end MIG welding processes.
- Built-in control box with service door and vandal resistant loss proof screw.
- Service door is contoured to the shape of the pole with rubber gasket.
- The control gear tray is prewired with MCB, terminal connectors for loop-in / loop-out arrangement.
- The foundation bolt holes in the base plate are designed to be elongated for fine adjustments / alignment of the pole during installation.
- Base plate made of steel grade E250 & foundation bolt of grade 4.6
-  - Conformity mark

Product Benefits

- Quick installation and low assembly costs.
- A wide range of Pole heights and bracket options to meet various lighting requirements.
- Functionally versatile, strong and stable.
- Long life span.
- Innovative design options to provide visual integration with the environment.
- Customised for your delight : Creating the entire product portfolio - Right from concept to completion, merging the best technology and practices in lighting.

Area of Application

Street lighting in main road / secondary roads, Illuminating pathways in parks, Gardens, Resorts, Private driveways, Residential Area Lighting, Boulevards, Building perimeters and Public places.

Installation

Surface mounted with base plate and fitted on a pre formed foundation.

Available Finish

Coated with zinc rich primer and finished using environmentally stable polyurethane based paint / Pure polyester powder coated of desired colour.

- RAL 9004 Black
- RAL 9007 Grey aluminium
- RAL 7016 Anthracite grey
- Graphite grey

CONICAL ARCH

Series

K-LITE

Code	Bottom Size	Height	Mounting
12077-600-G39-SA	Ø149	6000	F53.1
12077-700-G39-SA	Ø161	7000	F53.2
12077-800-G39-SA	Ø173	8000	F53.3
12077-900-G39-SA	Ø185	9000	F53.4

Street Light [G39]

For Pendant Type, Change G39 to G40

